

UMETA



UMETA Hermann Ulrichskötter
Metallwarenfabrik GmbH & Co. KG
Almestraße 1-3
33649 Bielefeld . Germany

Fon: +49 (0)521.948.0
Fax: +49 (0)521.948.111

**4 years warranty for all
UMETA TWIN-LOCK© Grease Guns**

Warning! **Safety instructions**

GB/0610

Please read the following warnings with utmost care:

UMETA lubrication products are capable of creating pressures well above 800 bar / 11,600 PSI.

- Make sure that every part of the system can withstand the anticipated pressures.
- Maintain your equipment periodically
- Check before each use that all connections are securely fastened.
- Only use components that show no indications of damage.

- Never point the outlet at yourself or others.
- Never touch a hose that is under pressure.

Hoses are subject to rapid aging.

- Never use a hose that is older than 3 years.
- Hoses must never be bent or twisted with force. The smallest turning radius is 100mm / 4".

Never operate UMETA pneumatic grease guns at air pressures above 10 bar / 145 PSI.

Special grease nipples may be required if you are using automated lubrication equipment. The impulse-like, high grease pressure may be too strong for ordinary fittings. Please check with us for the correct fittings for your system.

Use UMETA products only with genuine UMETA accessories that are explicitly designed for the intended purpose. Changing the UMETA construction may result in severe damage or injury. Seek immediate medical care after an injury. Be prepared to tell the doctor exactly what happened and what the substances were that you came into contact with in order to receive the right treatment.

UMETA products must never be brought in contact with dangerous or corrosive substances.

We make it move.

UMETA products are available from
MARYLAND METRICS
P.O. Box 261 Owings Mills, MD 21117 USA
ph: (410)358-3130 (800)638-1830 fx: (410)358-3142 (800)872-9329
web: <http://mdmetric.com> email: sales@mdmetric.com
RFQ form: <http://mdmetric.com/rfq.htm>