

DIN 28115

Medidas en milímetros
Dimensions in mm
Maße in mm

Bridas con cuello largo para soldar
Presion nominal 10

Long welding neck flanges
Rated pressure 10

Flanschtutzen
Nenndruck 10

| Diámetro Nominal Rated Diameter Nennweite | Presión de Servicio / Service Pressure / Betriebsdruck | | | Tubo / Pipe / Rohr | | | | Brida / Flange / Flansch | | | | Cuello / Neck / Ansatz | | Resalto / Raised face / Dichtleiste | | Tornillos / Screws / Schrauben | | | Peso de una brida / Weight of a flange / Gewicht eines Flansches (7,85 Kg/dm ³) Kg |
|-------------------------------------------------|--------------------------------------------------------------|--|--|--------------------------|----|-----|-----|-----------------------------|-----|-----|----|---------------------------|---|-------------------------------------------|--------------------------------|--------------------------------|--------------------------------|------|---------------------------------------------------------------------------------------------------------|
| | | | | a | s | D | j | b | h | m | r | g | f | k | Numero / Number / Anzahl | l | Rosca / Thread / Gewinde | | |
| 25 | 8 Kg/cm ² 200 °C | | | 38 | 7 | 115 | 24 | 16 | 120 | 50 | 8 | 68 | 2 | 85 | 4 | 14 | M 12 (1/2") | 1,7 | |
| 32 | | | | 51 | 8 | 140 | 35 | 16 | 120 | 62 | 8 | 78 | 2 | 100 | 4 | 18 | M 16 (5/8") | 2,8 | |
| 40 | | | | 57 | 8 | 150 | 41 | 16 | 120 | 70 | 8 | 88 | 3 | 110 | 4 | 18 | M 16 (5/8") | 3,2 | |
| 50 | | | | 70 | 8 | 165 | 54 | 18 | 120 | 85 | 8 | 102 | 3 | 125 | 4 | 18 | M 16 (5/8") | 4,2 | |
| 65 | | | | 89 | 8 | 185 | 73 | 18 | 170 | 104 | 8 | 122 | 3 | 145 | 4 | 18 | M 16 (5/8") | 6,8 | |
| 80 | | | | 102 | 8 | 200 | 86 | 20 | 170 | 118 | 8 | 138 | 3 | 160 | 4 | 18 | M 16 (5/8") | 7,8 | |
| 100 | | | | 121 | 10 | 220 | 101 | 20 | 170 | 138 | 8 | 158 | 3 | 180 | 8 | 18 | M 16 (5/8") | 9,7 | |
| 125 | | | | 146 | 10 | 250 | 126 | 22 | 170 | 164 | 10 | 188 | 3 | 210 | 8 | 18 | M 16 (5/8") | 11,6 | |
| 150 | | | | 171 | 10 | 285 | 151 | 22 | 170 | 188 | 10 | 212 | 3 | 240 | 8 | 23 | M 20 (3/4") | 14 | |
| 200 | | | | 224 | 10 | 340 | 204 | 22 | 170 | 246 | 10 | 268 | 3 | 295 | 8 | 23 | M 20 (3/4") | 20,4 | |

DIN 28115

Medidas en milímetros
Dimensions in mm
Maße in mm

Bridas con cuello largo para soldar
Presion nominal 25

Long welding neck flanges
Rated pressure 25

Flanschtutzen
Nenndruck 25

| Diámetro Nominal Rated Diameter Nennweite | Presión Nominal / Nominal pressure / Nenndruck | | | Presión de Servicio a 200° C / Service Pressure to 200° C / Betriebsdruck bis 200° C | | | Tubo / Pipe / Rohr | | | | Brida / Flange / Flansch | | | | Cuello / Neck / Ansatz | | Resalto / Raised face / Dichtleiste | | Tornillos / Screws / Schrauben | | | Peso de una brida / Weight of a flange / Gewicht eines Flansches (7,85 Kg/dm ³) Kg |
|-------------------------------------------------|------------------------------------------------------|--------------------|----|--------------------------------------------------------------------------------------------------|-----|----|--------------------------|-----|----|-----|-----------------------------|----|-----|---|---------------------------|----|-------------------------------------------|--------------------------------|--------------------------------|--------------------------------|--|---------------------------------------------------------------------------------------------------------|
| | | | | | | | a | s | D | j | b | h | m | r | g | f | k | Numero / Number / Anzahl | l | Rosca / Thread / Gewinde | | |
| | Kg/cm ² | Kg/cm ² | | | | | | | | | | | | | | | | | | | | |
| 25 | 16 | 25 | 40 | 32 | 38 | 7 | 115 | 24 | 18 | 120 | 50 | 8 | 68 | 2 | 85 | 4 | 14 | M 12(1/2") | 1,9 | | | |
| 32 | 16 | 25 | 40 | 32 | 51 | 8 | 140 | 35 | 18 | 120 | 62 | 8 | 78 | 2 | 100 | 4 | 18 | M 16(5/8") | 3 | | | |
| 40 | 16 | 25 | 40 | 32 | 57 | 8 | 150 | 41 | 18 | 120 | 70 | 8 | 88 | 3 | 110 | 4 | 18 | M 16(5/8") | 3,2 | | | |
| 50 | 16 | 25 | 40 | 32 | 70 | 8 | 165 | 54 | 20 | 120 | 85 | 8 | 102 | 3 | 125 | 4 | 18 | M 16(5/8") | 4,5 | | | |
| 65 | 16 | . | . | 13 | 89 | 8 | 185 | 73 | 22 | 170 | 104 | 8 | 122 | 3 | 145 | 4 | 18 | M 16(5/8") | 7,5 | | | |
| | . | 25 | 40 | 32 | 89 | 8 | 185 | 73 | 22 | 170 | 104 | 8 | 122 | 3 | 145 | 8 | 18 | M 16(5/8") | 7,3 | | | |
| 80 | 16 | . | . | 13 | 102 | 8 | 200 | 86 | 24 | 170 | 118 | 8 | 138 | 3 | 160 | 8 | 18 | M 16(5/8") | 8,4 | | | |
| | . | 25 | 40 | 32 | 102 | 8 | 200 | 86 | 24 | 170 | 118 | 8 | 138 | 3 | 160 | 8 | 18 | M 16(5/8") | 8,4 | | | |
| 100 | 16 | . | . | 13 | 121 | 10 | 220 | 101 | 24 | 170 | 138 | 8 | 158 | 3 | 180 | 8 | 18 | M 16(5/8") | 9,8 | | | |
| 125 | 16 | . | . | 13 | 146 | 10 | 250 | 126 | 26 | 170 | 164 | 10 | 188 | 3 | 210 | 8 | 18 | M 16(5/8") | 12,6 | | | |
| 150 | 16 | . | . | 13 | 171 | 10 | 285 | 151 | 28 | 170 | 188 | 10 | 212 | 3 | 240 | 8 | 23 | M20 (3/4") | 15,8 | | | |
| 200 | 16 | . | . | 13 | 224 | 10 | 340 | 204 | 34 | 170 | 246 | 10 | 268 | 3 | 295 | 12 | 23 | M20 (3/4") | 24,2 | | | |

